

Nuvola Duo-tec



- Digital control panel with back-lighted LCD display
- Wide modulation ratio up to 1÷7: better efficiency thanks to reduced switch-on/switch-off of the boiler
- Gas Adaptive Control (GAC) system: combustion automatic control to maintain constantly the highest level of efficiency
- Modulating circulating pump
- High DHW performances: up to 500 lt in 30 minutes (ΔT 30°C)
- Stainless steel 45 lt cylinder
- Frontal access for advanced diagnostics
- DHW expansion vessel supplied with the boyler Nuvola Duo-tec 33 GA VES



Diagnostics
on the control panel there is easy access for the diagnostics.
With a USB connection it is possible to check single boilers or multiple boilers functions.



Modulation ratio
the modulation system is able to adapt the heat output to the energy demanded by the building.

Hydraulic system

3 way electric diverter valve
Stainless steel premixing burner
Stainless steel heat exchanger
Stainless steel tank
Modulating fan with electronic speed adjusting system
Automatic by-pass
Modulating low energy pump of the heating circuit with built-in air vent
System to prevent pump and diverter valve sticking operating every 24 hours
Central relief valve set at 3 bar
Tank relief valve set at 8 bar
Sanitary 2 litres expansion vessel available as optional
Sanitary recirculation option

Thermoregulation system

Built-in climatic regulation (outdoor sensor available as optional)
Control of multi-zones system option

Control system

Overheat limit thermostat of the water/flue exchanger
Hydraulic pressure switch to prevent boiler operating in event of low water
Overheat limit thermostat against flues overheat
Electronic temperatures control by NTC sensors
Anti legionella function
Full anti-frost device
Electronic thermometer
Digital heating circuit pressure gauge

	Combi with DHW storage		
Product code	16 GA	24 GA	33 GAVES
Maximum DHW heat input	kW	16,5	24,7
Maximum heating heat input	kW	12,4	20,6
Maximum DHW heat output	kW	16	24
Maximum heating heat output 80/60°C	kW	12	20
Maximum heating heat output 50/30°C	kW	13,1	21,8
Minimum heating heat output 80/60°C	kW	2,2	3,4
Minimum heating heat output 50/30°C	kW	2,4	3,7
Energetic efficiency (92/42/CEE)			
Average efficiency (DIN 4702-T8)	%	109,8	109,8
Nominal efficiency 80/60°C	%	97,8	97,7
Nominal efficiency 50/30°C	%	105,8	105,8
Efficiency 30%	%	107,8	107,6
NOx class (EN 483)		5	5
Minimum working temperature	°C	-5	-5
Expansion vessel capacity/pre-charge	l/bar	7,5/0,8	7,5/0,8
Heating temperature range	°C	25/80	25/80
DHW temperature range	°C	35/60	35/60
Tank capacity	l	45	45
Tank expansion vessel capacity/pre-charge	l/bar	2/2,5	2/2,5
Specific flow rate (EN 625)	l/min	13,3	16,6
DHW production ΔT 25°C ⁽¹⁾	l/min	9,2	13,8
DHW production at discharge ΔT 30°C ⁽¹⁾	l/30'	275	385
Maximum pressure heating circuit	bar	3	3
Maximum pressure DHW circuit	bar	8	8
Coaxial flue system Ø 60/100 max length	m	10	10
Dual flue system Ø 80 max length	m	80	80
Maximum flue mass flow rate	kg/s	0,008	0,012
Minimum flue mass flow rate	kg/s	0,001	0,002
Maximum flue temperature	°C	75	80
Dimensions (h x w x d)	mm	950 x 600 x 466	950 x 600 x 466
Net weight	Kg	62	62
Gas type		Natural gas/LPG	Natural gas/LPG
Power consumption	W	112	102
Grade of protection		IPx5D	IPx5D

⁽¹⁾without flow restrictor.